



Scapa 2721

PVC Lane Marking Adhesive Tape

DESCRIPTION

Scapa 2721 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubberbased adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability for use in lane marking and flooring applications

APPLICATIONS

- General splicing
- Flooring and lane marking
- Colour coding

PRODUCT BENEFITS

- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)
- Environmentally friendly technology
- Easy transversal tearability
- Excellent conformability
- Suitable for indoor and protected outdoor environments
- Excellent resistance to abrasion, corrosion and moisture

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Tensile Strength	25	N/cm	CEI EN 60454
Nominal Thickness	0.16	mm	CEI EN 60454
Elongation at Break	150	%	CEI EN 60454
Adhesion to Steel	1.5	N/cm	CEI EN 60454
Adhesion on Backing	1.5	N/cm	CEI EN 60454

STANDARD PRESENTATIONS

- Roll Width: 50, 75 and 100mm
- Roll Length: 33 metres
- Packaging: Heat shrink sleeve
- Core: 76mm Scapa branded cardboard core
- Colours: Black, Yellow, White, Red, Blue, Light green

RECOMMENDATIONS

Rolls should be stored at on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months of receipt. The tape should be applied with sufficient pressure to ensure an optimum bonding and prevent ageing effects. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.