

Technical Data

Issue 10 February 2000

AT160 Waterproof Cloth Tape

General description

A polythene extruded cloth tape, coated on one side with a waterproof finish and on the other with an aggressive pressure sensitive adhesive.

- Matt finish.
- Easy tear.
- Easy unwind.
- Conformable to awkward shapes.
- Strong.
- Water resistant finish.
- Good abrasion resistance.
- Non-corrosive adhesive.
- Can be written on.

Specifications

Certification* to the following standards may be available on request.
DEF STAN 81-25 and BS3887 : 1991

Technical Details

Typical values

Thickness	0.33mm
Breaking Load	85 N/cm
Elongation	8%
Adhesion	
Steel	4.0 N/cm
Self	2.2 N/cm
Moisture Vapour Permeability	35g/m ² /24hrs
Water extract	
PH	6.5 to 7.5
Chloride Max.	0.05% as NaCl
Sulphate Max.	0.25% as Na ₂ SO ₄
Service Temp	-50°C to +80°C
Application Temp	+10°C to +45°C

*Standard charge for certificate: £25.00.



NOTE

Except where indicated otherwise, the above figures are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

 **ADVANCE**
adhesive tapes



BS EN ISO 9002
Q05206



INVESTOR IN PEOPLE

AFERA

Association des Fabricants Européens de
Rubans Auto-Adhésifs.

Advance Tapes International Limited, PO Box 122,
Abbey Meadows, Leicester, LE4 5RA.
Tel: 0116 251 0191. Fax: 0116 265 2046. www.advancetapes.com