



UNIT 11, BUCKINGHAM SQUARE, HURRICANE WAY,
WICKFORD, ESSEX SS11 8YQ

Tel: (01268) 572255
Fax: (01268) 572121
E-mail: david@hadleigh.u-net.com
Web: www.hadleigh.uk.com

TECHNICAL DATA

H132H

PRODUCT:

“HADLEIGH GREEN” SILICONE TAPE

DESCRIPTION:

H132H Green Polyester Silicone Tape is based on a 50 micron Polyester Film coated with a specially formulated Silicone adhesive.

APPLICATION:

H132H is ideal for very high temperature masking for Powder Coating, Anodizing, PCB fabrication and is chemically resistance, which can be supplied in Roll, Disc or Die Cut form.

FEATURES AND BENEFITS:

Its Silicone Adhesive leaves no residue during removal from the coated substrate.
Provides high UV and chemical resistance and durability.

TECHNICAL DATA:

Temperature Range:	-51°C to +204°C
Tape Thickness	0.089mm
Backing Thickness	0.05mm
Tensile strength	216 N/25mm
Elongation at break	100%
Adhesion to Steel	11.1 N/25mm
Dielectric Strength	6 kV

The data given herewith represent average values and should not be taken to write technical specifications. They are put forward in good faith but are not guaranteed. In particular the Customer should satisfy themselves of the suitability of the product for its intended use.

Storage should be in a dry well ventilated room in their initial packaging with a reasonable constant temperature around 20°C. The product should always be applied to clean, dry surfaces.