

HADLEIGH Enterprises Limited

UNIT 11, BUCKINGHAM SQUARE, HURRICANE WAY,
WICKFORD, ESSEX SS11 8YQ

Tel: (01268) 572255
Fax: (01268) 572121
E-mail: sales@hadleightapes.co.uk
Web: www.hadleigh-tapes.co.uk

TECHNICAL DATA

H133

PRODUCT:

POLYESTER THERMOSETTING TAPE

DESCRIPTION:

H133 Polyester Thermosetting Tape is based on a 0.023mm thick Polyester film coated with a natural thermosetting adhesive.

Colours: Yellow, Clear or Black.

APPLICATION:

This polyester thermosetting tape is a general purpose tape widely used as an insulating medium in capacitor and wound component manufacture.

TECHNICAL DATA:

Film thickness	23 microns
Total thickness	60 microns
Elongation at break	90%
Temperature range:-	
Continuous working	130°C
Steel adhesion	40 N/25mm
Dielectric Strength	4500 volts
Breakdown voltage	4.5 kV

UL Approval file No. E178430

The data given herewith represent average values and should not be taken to write technical specifications. They are put forward in good faith but are not guaranteed. In particular the Customer should satisfy themselves of the suitability of the product for its intended use.

Storage should be in a dry well ventilated room in their initial packaging with a reasonable constant temperature around 20°C. The product should always be applied to clean, dry surfaces.